



PERSONAL  
COMPUTERS



SMALL  
COMPUTERS  
NETWORK

# iDialog

## 400-1600 VA single-phase

iDialog 400-1600 VA



The **iDialog** UPS has been designed to protect PCs and critical peripherals in home and small office environments. iDialog is easy to install and provides powerful, economic protection for:

- IT equipment including PCs, Media Centers, PoE, VoIP and other such peripherals.
- TVs, Home Cinemas, Satellite and Digital Terrestrial receivers, DVD readers and writers.
- Modems and xDSL routers.
- Small household appliances.

### CHARACTERISTICS

- Maximum power protection with **PowerShield<sup>3</sup>** UPS monitoring and shutdown software available for free download from our website [www.riello-ups.com](http://www.riello-ups.com)

- Suitable for installation on PCs running Windows 7, 2008, Vista, 2003, Xp, Linux, Mac OSX and Sun Solaris operating system.
- Compact dimensions and ergonomic design: **iDialog** can be placed on a desk top or other convenient location, with easy to access connections and informative front panel.
- Silent running: iDialog can be used to protect other sensitive electronic devices including Home Cinemas, CD Writers, DVD players, Satellite and Digital Terrestrial receivers.

### 2 YEAR WARRANTY

MODELS	ID 40	ID 60	ID 80	ID 120	ID 160
POWER	400VA/240W	600VA/360W	800VA/480W	1100VA/660W	1600VA/960W
<b>INPUT</b>					
Rated voltage	220-240 Vac				
Input voltage tolerance	230 Vac (+20/-25%)				
Frequency	50/60 Hz with auto sensing				
<b>OUTPUT</b>					
Voltage during mains operation	230 Vac (+20/-25%)				
Voltage during battery operation	230 Vac (+/- 10%)				
Frequency during battery operation	50 or 60 Hz (+/- 1%)				
<b>BATTERIES</b>					
Type	VRLA AGM Maintenance-free lead-acid				
Recharge time	6-8 h				
<b>ENVIRONMENTAL</b>					
Net weight (kg)	3.2	3.4	6.6	7	
Gross weight (kg)	3.7	4.1	8.1	8.6	
Dimensions (hwd) (mm)	192 x 90 x 232			275 x 97 x 315	
Packaging dimensions (hwd) (mm)	278 x 300 x 138			370 x 400 x 170	
Communication	USB				
Output sockets	4 IEC			6 IEC	
Compliance	EN 62040-1-1 and Directive 2006/95/EC; EN 62040-3 EN 62040-2 and Directive 2004/108 EC				
Marks	CE; GS/Nemko				
Operating temperature	0°C / +40°C				
Colour	Black				
Altitude and relative humidity	6000 meters max. elevation, < 95% non condensing				
Accessories provided	2 output supply cables, 1 USB cable, user guide				

